

# FN1010 Load Pin



- Load Pin Design
- Range from 10 to 2000 kN (2 to 400 klbf)
- Other Ranges on Request
- Voltage or Current Output

## DESCRIPTION

Measurement-Specialties' load pins, model FN1010, are designed to fit in the place of the regular mounting unit. The implantation is facilitated by the possibility of modifying a certain number of dimensions. The FN1010 is suitable for numerous applications on lifting motors and handling equipment. The load pins can be used to measure forces on rotating components (pulleys, sheaves, etc.) and can be directly mounted on shackles.

The sensing element is fitted with thin film strain gauges in a Wheatstone bridge circuit. All FN1010 Load Pins incorporate a keyed anti-rotation slot. Optionally, the load pins may be made watertight for certain applications while resting insensitive to hydrostatic pressure effects. Additionally, the FN1010 is available with an integrated high-level analogue output.

With many years of experience as a designer and manufacturer of sensors, Measurement-Specialties often works with customers to design or customize sensors for specific uses and testing environments.

To meet your needs we also offer complete turnkey systems. The matched components (sensor, power, amplifier and digital display) are formatted, calibrated and ready for immediate use.

## FEATURES

- Full Scale Range : from 0-10 to 0-2000 kN (0-2 to 0-400 klbf)
- Tension and Compression
- Optional: Watertight
- High Coefficient of Security
- Optional: Watertight
- Bidirectional Versions Available
- Level Output Model with Integrated Amplifier

## APPLICATIONS

- Crane Monitoring
- Building Machine Monitoring
- Load-Limited Device
- Offshore

## STANDARD RANGES

<b>Ranges in N</b>	10k	20k	50k	100k	200k	500k	1 000k	2 000k
<b>Ranges in lbf</b>	2k	4k	10k	20k	40k	100k	200k	400k

# FN1010 Load Pin

## PERFORMANCE SPECIFICATIONS

**Ambient Temperature: 20±1° C (unless otherwise specified)**

PARAMETERS	
Operating Temperature Range (OTR)	-20 to 80° C [-4 to 176° F]
Compensated Temperature Range (CTR)	0 to 60° C [32 to 140° F]
Zero Shift in CTR	<0.5% F.S. / 50° C [100° F]
Sensitivity Shift in CTR	<1% of reading / 50° C [100° F]
Range (F.S.)	0-10 to 0-2000 kN [0-2 to 0-400 klb <sub>f</sub> ]
Over-Range	
Without Damage	1.5 x F.S.
Without Destruction	5 x F.S.
Accuracy	
Combined Non-Linearity & Hysteresis	±1% F.S.

### Electrical Characteristics

Model	FN1010	FN1010-A1	FN1010-A2	FN1010-A3 (2 wires)
Supply Outage	10Vdc	10–30Vdc	±15Vdc (±12 to ±18Vdc)	12-36Vdc
F.S. Output	±1.5mV/V	±2V ±5% F.S.	±5V ±5% F.S.	4–20mA (4-12-20)
Zero Offset	<±5% F.S.	2.5V ±5% F.S.	0V ±5% F.S.	4 (or 12mA)
Input Impedance/Consumption	350 to 700Ω	<50mA	<50mA	-
Output Impedance	350 to 700Ω	<10Ω	<10Ω	-
Insulation under 50Vdc	≥100MΩ	≥100MΩ	≥100MΩ	≥100MΩ

### Notes

1. Electrical Termination: Shielded cable; standard length 2m [6.5ft]
2. Materials: Body in stainless steel

# FN1010 Load Pin

## DIMENSIONS & WIRING SCHEMATIC (IN METRIC AND IMPERIAL)

All dimensions correspond to a standard. They can be modified, if necessary, for mounting. Please consult us for details.

In order to simplify the use of load pins and limit the mechanical modifications associated with their implantation, all dimensions are given between two limits within which performances and characteristics can be maintained without increasing financial cost to the user.

**Note:** The delimiter groove can be placed on the output cable side.

### Wiring Schematic

**FN1010**

**FN1010-A1**

**FN1010-A2**

Dimensions in mm [inch]


F.S. Ranges in N [Lbf]		10k [2k]		20k [4k]		50k [10k]		100k [20k]		200k [40k]		500k [100k]		1000k [200k]		2000k [400k]	
A	Min.	22	[0.87]	27	[1.06]	30	[1.18]	42	[1.65]	54	[2.13]	82	[3.23]	110	[4.33]	150	[5.91]
	Nominal	25	[0.98]	30	[1.18]	35	[1.38]	45	[1.77]	60	[2.36]	90	[3.54]	120	[4.72]	160	[6.30]
	Max	30	[1.18]	35	[1.38]	40	[1.57]	50	[1.97]	65	[2.56]	100	[3.94]	130	[5.12]	170	[6.69]
B	Min.	25	[0.98]	25	[0.98]	30	[1.18]	40	[1.57]	50	[1.97]	65	[2.56]	80	[3.15]	120	[4.72]
	Nominal	30	[1.18]	30	[1.18]	40	[1.57]	50	[1.97]	70	[2.76]	90	[3.54]	110	[4.33]	160	[6.30]
	Max.	35	[1.38]	35	[1.38]	50	[1.97]	65	[2.56]	90	[3.54]	115	[4.53]	140	[5.51]	200	[7.87]
C	Min.	10	[0.39]	10	[0.39]	15	[0.59]	20	[0.79]	25	[0.98]	30	[1.18]	40	[1.57]	60	[2.36]
	Nominal	15	[0.59]	15	[0.59]	20	[0.79]	25	[0.98]	30	[1.18]	40	[1.57]	55	[2.17]	80	[3.15]
	Max.	20	[0.79]	20	[0.79]	25	[0.98]	30	[1.18]	35	[1.38]	50	[1.97]	70	[2.76]	100	[3.94]
D	D	3	[0.12]	3	[0.12]	4	[0.16]	5	[0.20]	5	[0.20]	5	[0.20]	5	[0.20]	5	[0.20]
E	E	5	[0.20]	5	[0.20]	5	[0.20]	10	[0.39]	10	[0.39]	10	[0.39]	15	[0.59]	15	[0.59]

# FN1010 Load Pin

## OPTIONS

A1 : Unipolar Tension
A2 : Bipolar Tension
1. A3 : Current output (2 wires)

## ORDERING INFO



### NORTH AMERICA

Measurement Specialties Inc.  
1000 Lucas Way  
Hampton, VA 23666  
USA  
Tel: 1-757-766-1500  
Fax: 1-757-766-4297  
Sales: pvg.cs.amer@meas-spec.com

### EUROPE

Measurement Specialties  
(Europe), Ltd.  
26 Rue des Dames  
78340 Les Clayes-Sous-Bois,  
France  
Tel: +33 (0) 130 79 33 00  
Fax: +33 (0) 134 81 03 59  
Sales: pfg.cs.emea@meas-spec.com

### ASIA

北京赛斯维测控技术有限公司  
北京市朝阳区望京西路48号  
金隅国际C1002  
电话 : +86 010 8477 5646  
传真 : +86 010 5894 9029  
邮箱 : [sales@sensorway.cn](mailto:sales@sensorway.cn)  
<http://www.sensorway.cn>

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.